


PRODUCT FEATURES

- ☑ Ultrafast Reverse Recovery Time
- ☑ Soft Reverse Recovery Characteristics
- ☑ Low Reverse Recovery Loss
- ☑ Low Forward Voltage
- ☑ High Surge Current Capability
- ☑ Low Inductance Package

APPLICATIONS

- ☑ Inversion Welder
- ☑ Uninterruptible Power Supply (UPS)
- ☑ Plating Power Supply
- ☑ Ultrasonic Cleaner and Welder
- ☑ Converter & Chopper
- ☑ Power Factor Correction (PFC) Circuit



ABSOLUTE MAXIMUM RATINGS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
V_R	Maximum D.C. Reverse Voltage		45	V
V_{RRM}	Maximum Repetitive Reverse Voltage		45	V
$I_{F(AV)}$	Average Forward Current	$T_C=100^{\circ}\text{C}$, Per Diode	300	A
		$T_C=100^{\circ}\text{C}$, Per Moudle	600	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=100^{\circ}\text{C}$, Per Diode	420	A
I_{FSM}	Non-Repetitive Surge Forward Current	1/2 Cycle, 60Hz, Sine	6600	A
I^2t	I^2t (For Fusing)	$T_J=45^{\circ}\text{C}$, $t=8.3\text{ms}$, 60Hz, Sine	130050	A^2s
P_D	Power Dissipation		225	W
T_J	Junction Temperature		-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range		-40 to +125	$^{\circ}\text{C}$
V_{iso}	Insulation Test Voltage	AC, $t=1\text{min}$	3000	V
Torque	Module-to-Sink	Recommended (M6)	3~5	N.m
Torque	Module Electrodes	Recommended (M6)	3~5	N.m
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	0.12	$^{\circ}\text{C}/\text{W}$
Weight			155	g

ELECTRICAL CHARACTERISTICS

$T_C=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=45\text{V}$	--	--	0.3	mA
		$V_R=45\text{V}, T_J=125^\circ\text{C}$	--	--	2	mA
V_F	Forward Voltage	$I_F=300\text{A}$	--	0.50	--	V
		$I_F=300\text{A}, T_J=125^\circ\text{C}$	--	0.45	--	V




Figure 1. Forward Voltage Drop vs Forward Current




Figure 2. Reverse Recovery Charge vs dI_F/dt




Figure 3. Reverse Recovery Current vs dI_F/dt




Figure 4. Forward current vs Case temperature





Figure 5. Transient Thermal Impedance

Package Outlines



Unit:mm